



AI LINK

For H3 Pro, R series parallel installation



IP65 RATED

High level of protection, suitable for outdoor installation.



WIDE OPERATING TEMPERATURE RANGE

Wide operating temperature range, suitable for a variety of environments.



SAFE AND RELIABLE

Safe, reliable and highly compatible.



For more information about the Fox ESS range, visit:
www.fox-ess.com

TECHNICAL SPECIFICATIONS

MODEL		A-1000
COMMUNICATION		
		30
		4, modbus RTU, sunspec, 9600bps, 19200bps, 38400bps, 57600bps, 115200bps
		2, RJ45, 10M/100M
		6 ~ 24
		3, Relay
		LTE-FDD: B1, B3, B7, B8, B20, B28A
		LTE-TDD: B38,B40,B41
		WCDMA: B1,B8
		802.11 b / g / n / ac
		HT20 / 40 MHz
		2.4GHz
INDICATOR LIGHTS		
LED		3 LEDs
Button		Start
POWER		
DC Input Voltage [Vdc]		10 ~ 27
Consumption [W]		Standard 20, Max<30
ENVIRONMENTAL CONDITION		
Working Temperature [°C]		-30 ~ +60
Storage Temperature [°C]		-40 ~ +70
Relative Humidity [%]		≤95 (No Condensation)
Altitude [m]		≤4000
Ingress Protection		IP65
GENERAL PROPERTY		
Dimention (W*H*D) [mm]		260*192*88
Weight [kg]		2.5
Installation Method		Wall mount, indoor, outdoor